

Crystal LTD TM SPEC Form

[www.crystaltherm.com](http://www.crystaltherm.com)

Customer


PO#

PO date

Thermoelectric module (TM) specification

| PO position # | TM          | Internal Solder Melting Temp, C | Max operating temperature, °C |                      | Parameters in vacuum at hot side temperature 25 °C |                      |                      |                       | Rac at 25 °C          |                | Ceramic size, mm |    | TM Height  |                   | Wire               |            |                 | Sealing |
|---------------|-------------|---------------------------------|-------------------------------|----------------------|--|----------------------|----------------------|-----------------------|-----------------------|----------------|------------------|----|------------|-------------------|--------------------|------------|-----------------|---------|
|               |             |                                 | short peak                    | continuous operation | I <sub>max</sub> , A                               | U <sub>max</sub> , V | Q <sub>max</sub> , W | dT <sub>max</sub> , K | R <sub>ac</sub> , Ohm | Tolerance ±, % | A/A1             | B  | Height, mm | Tolerance t, ± mm | S, mm <sup>2</sup> | Length, mm | Tolerance ±, mm |         |
| 1             | S-127-07-10 | 138                             | 130                           | 115                  | 2.2  | 16.2                 | 22.6                 | 72.5                  | 5.45                  | 10             | 20/20            | 20 | 2.40       | 0.2               | 0.14               | 100        | 1               |         |
|               |             |                                 |                               |                      |  |                      |                      |                       |                       |                |                  |    |            |                   | MGTF (teflon)      |            |                 |         |
|               |             |                                 |                               |                      |  |                      |                      |                       |                       |                |                  |    |            |                   |                    |            |                 |         |
|               |             |                                 |                               |                      |  |                      |                      |                       |                       |                |                  |    |            |                   |                    |            |                 |         |
|               |             |                                 |                               |                      |  |                      |                      |                       |                       |                |                  |    |            |                   |                    |            |                 |         |
|               |             |                                 |                               |                      |  |                      |                      |                       |                       |                |                  |    |            |                   |                    |            |                 |         |

Clamping force: 1.5 - 15.0 kg



[www.crystaltherm.com](http://www.crystaltherm.com)

Max dT is reduced by 2-3K for silicon sealed and 1-2K for epoxy sealed versions.



### U(dT) at $T_{hot}=298K$

